

TUMBLE DRYERS

TRD 28 · 33



STANDARD FEATURES & BENEFITS

- Tumble dryer in skin plate, cream color
- Big loading door (opening of 180°)
- Transmission by pulley and belt
- Time and temperature selection
- Reverse drum: all models offer the reverse turning of the drum
- Drum in galvanised steel
- Digital control and electronic control. Easy and intuitive to use, the electronic control offers a complete control of the process
- Radial airflow circuit
- New filter drawer with wide surface and improved airflow, filter grid is standard 0,3 mm
- Cool down: anti-wrinkle at the end of cycle
- Models available in electric, gas or steam heating
- Self-Service: Digital range has several payment options for laundromats; to work with centralized payment systems, with coin / token, or with prepaid card systems. Electric and gas heated models for self-service available

OPTIONS

- Moisture control
- Double doorglass
- Stainless steel drum with mixed axial-radial flow and punched drum holes
- Stainless steel body
- Stainless steel front panel
- Low pressure steam battery
- Opposite door opening
- Lint filter with dia. 0,6 or 1,2 mm mesh
- Wooden box packing
- Special voltages
- Mechanical meter for coin / token
- Electronic coin kit

TOLON

TUMBLE DRYERS

TRD 28 · 33

MODEL	UNIT	TRD 28	TRD 33
Capacity 1/18	kg	31	37
Capacity 1/20	kg	27,5	33
Hourly output *	kg/h	59,3	63,9
Evaporation capacity *	l/h	30,9	32,1
DRUM		1100	1300
Ø Drum	mm	947	947
Ø Door	mm	802	802
Center door height	mm	1.040	1.040
Bottom door height	mm	640	640
Drum depth	mm	780	936
Drum volume	l	550	660
POWER		550	675
Drum motor	kW	0,55	0,55
Fan motor	kW	0,55	0,55
Electric heating	kW	30	36
Total electric power (elec. model)	kW	31,15	37,15
Gas heating	kW	41	41
Steam heating	kW	50,1	50,1
CONNECTIONS		ELECTRICAL - STEAM/GAS	ELECTRICAL - STEAM/GAS
Tension 230V - I + N + T	No x mm2 / A	- 3 x 1,5 / 20A	- 3 x 1,5 / 20A
Tension 230V - III + T	No x mm2 / A	4 x 35 / 100A 3 x 1,5 / 20A	4 x 50 / 125A 3 x 1,5 / 20A
Tension 400V - III + N + T	No x mm2 / A	5 x 16 / 63A 3 x 1,5 / 20A	5 x 16 / 63A 3 x 1,5 / 20A
Ø Gas inlet	BSP	1/2"	1/2"
Ø Steam inlet	BSP	1"	1"
Ø Condensed (Steam models)	BSP	1"	1"
DIMENSIONS / PACKING DIMENSIONS			
Net Width / Gross Width	mm	985 / 1.065	985 / 1.065
Net Depth / Gross Depth	mm	1.054 / 1.154	1.210 / 1.310
Net Height / Gross Height	mm	1946 / 2.080	1946 / 2.080
Net Weight / Gross Weight	kg	230 / 260	260 / 285
OTHERS			
Max airflow	m³/h	1.200	1.200
Ø Fume exhaust	mm	200	200
Sound level	dB	65	65

* It may vary depending on the type of heating, filter cleanliness or extraction type.

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding



Shorrock Trichem

Chanters Industrial Estate, Atherton, Manchester, M46 9SD

Tel: 01942 872 999 - E-mail: washcraft@shorrocktrichem.com